



DECLARATION OF PERFORMANCE

in accordance with EU Construction Products Regulation (CPR) no 305/2011
and Commission Delegated Regulation (EU) No 574/2014

No. DoP_DK_16021000_EN 13055-2_UK_Ver2

- Unique identification code of the product-type:*
16021000_EN 13055-2, Leca® 4-10 rund, Leca® Medium
- Intended use/s:*
Expanded clay lightweight aggregate for unbound and hydraulically bound applications in buildings, roads and civil engineering works
- Manufacturer:*
Leca Danmark A/S
Randersvej 75
DK-8940 Randers SV,
Denmark
Phone: +45 87 61 02 01
Web: www.leca.dk
- Authorised representative:*

Leca Norge AS Årensvegen 1 2009 Nordby, Norway Phone: +47 4148 7100 Web: www.leca.com	Leca Sverige AB Box 6103 580 06 Linköping Sweden Phone +46 3186 7727 Web: www.leca.com	Fibo ExClay Deutschland GmbH Rahdener Strasse 1 21759 Lamstedt Germany Phone +49 4773 896 0 Web: www.leca.com	Leca UK Regus House, Herons Chester Business Park Chester, CH4 9QR UK Phone +44 844 3351 770 Web: www.leca.com
---	--	---	---

- System/s of AVCP:*
System 4
- Harmonised standard:*
EN 13055-2:2004



7. Declared performance/s:

Essential characteristics		Performance
Loose bulk density		305 kg/m ³ +/- 15 %
Particle size	4 - 10 mm	<d - D> mm
Particle shape		Round
Water absorption/ suction	Water absorption 5 min.	NPD
	Water absorption 60 min.	NPD
	Water absorption 24 hours	NPD
	Water suction height	NPD
Resistance to fragmentation/ crushing		> 0,82 N/mm ²
Percentage of crushed particles		NPD
Volume stability		NPD
Durability against freeze/thaw/weathering		Durable according to long term experience in Nordic climate
Composition/content	Chloride	< 0,02 %
	Acid soluble sulfate	< 0,5 % SO ₃
	Total sulfur	< 0,32 % S
Cleanliness		NPD
Release of heavy metals by leaching		NPD
Release of other dangerous substances		NPD

8. *Appropriate Technical Documentation and/or Specific Technical Documentation:*
Not applicable

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:


Plant Manager Jakob D. Knudsen
(name)

Randers
(place)

2020.01.01
(date of issue)



CE-marking


<p>Leca Danmark A/S Randersvej 75, Hinge DK-8940 Randers SV</p> <p>18</p> <p>DoP_DK_16021000_EN 13055-2</p>
<p>EN 13055-2</p> <p>16021000_EN 13055-2, Leca® 4-10 rund, Leca® Medium</p> <p>Intended use(s): Expanded clay lightweight aggregate for unbound and hydraulically bound applications in buildings, roads and civil engineering works</p>
<p>Declared performance:</p> <p>See section 7 of Declaration of Performance</p>
<p>Declaration of Performance and CE-marking can be found at www.leca.dk or sent on request.</p>